

INTERNAL TENON ADAPTER FOR SQUARE & ROUND POLES

	<p>4" Square Pole Mount With 2-3/8" O.D. Tenon Adapter NO. M-4SQ-SP-D Finish: Dark Bronze USE: Mount inside of 4" square pole. Furnished with four 5/16" hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.</p>		<p>4" Round pole mount with 2-3/8" O.D. Tenon Reducer NO. M-4SQR-SP-D Finish: Dark Bronze USE: This Tenon reducer is used over 4" non-tapered round pole. Furnished with three 3/18" hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.</p>
	<p>5" Square pole mount with 2-3/8" O.D. Tenon Adapter NO. M-5SQ-SP-D Finish: Dark Bronze USE: Mount inside of 5" square pole. Furnished with four 5/16" hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.</p>		<p>5" Round pole mount with 2-3/8" O.D. Tenon Reducer NO. M-5SQR-SP-D Finish: Dark Bronze USE: This Tenon reducer is used over 5" non-tapered round pole. Furnished with three 3/18" hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.</p>

EXTERNAL TENON BRACKET

	<p>90° Wall Mount with 2-3/8" O.D. Tenon Bracket NO. M-WM-SP-D Finish: Dark Bronze USE: The 90° wall mount with 2-3/8" tenon bracket attaches an Baseline Flood light to almost any surface: wall, roof, or wood pole. Provides wiring access and a built-in 2-3/8" O.D. tenon to mount a fixture with our adjustable slipfitter. Suggested 3/8" diameter bolts for mounting. Mounting holes are spaced 3-1/4" apart.</p>		<p>Horizontal Wall and Square pole mount with 2-3/8" O.D. Tenon Bracket NO. M-QS-SP-D Finish: Dark Bronze USE: This Tenon bracket can be installed onto a wall or square pole, that used for mounting a Baseline Flood light with an adjustable slipfitter.</p>
	<p>Pole top bracket accessories-Tenon & Yoke Adapter NO. M-SP-TR-D Finish: Dark Bronze USE: The 2-3/8" O.D. Tenon Mount Adapter for Yoke Fixtures is designed to mount Baseline light fixtures that are equipped with a yoke mount onto a 2-3/8" O.D. tenon. It may be utilized with the Flood Light Series of light fixtures.</p>		

ROUND EXTERNAL MOUNT HORIZONTAL TENON

	<p>Twin Spoke 90° Horizontal Tenon Adapter NO. M-R60-SP2-90-D Finish: Dark Bronze USE: The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Two fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally.</p>		<p>Triple Spoke 120° Horizontal Tenon Adapter NO. M-R60-SP3-120-D Finish: Dark Bronze USE: The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Three fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally.</p>
	<p>Twin Spoke 180° Horizontal Tenon Adapter NO. M-R60-SP2-180-D Finish: Dark Bronze USE: The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Two fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally.</p>		<p>Quad spoke 90° Horizontal Tenon Adapter NO. M-R60-SP4-90-D Finish: Dark Bronze USE: The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Four fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally.</p>
	<p>Triple Spoke 90° Horizontal Tenon Adapter NO. M-R60-SP3-90-D Finish: Dark Bronze USE: The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Three fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally.</p>		