

PROJECT NAME: \_\_\_\_\_

CATALOG #: \_\_\_\_\_

NOTES: \_\_\_\_\_

DATE: \_\_\_\_\_

## BLS-VTLS VAPOR TIGHT LINEAR SERIES

The BLS-VTLS Vapor Tight fixture is built to endure challenging environments and comes in both 4-foot and 8-foot sizes. Its housing is crafted from high-quality, pure PC material, ensuring outstanding stability and durability. Additionally, it features a stainless steel clip for effortless assembly and installation. This fixture offers the convenience of lumens adjustment and color temperature customization within a single unit, thereby significantly reducing the need for various product variants. Optional features like Emergency Battery Back Up and sensors are also available.



### SPECIFICATIONS FEATURES

**Construction:**

- Closed housing is ealed against moisture and environmental contaminants.
- Stainless steel clamp design, convenient assembly and separation of lamp body.
- 4 feet and 8 feet are available.

**Optics:**

- Up to 90W output 12800 lumens
- Adjustable lumen output with three lumen gears
- Switchable color temperature 3500K/4000K/5000K

**Electrical:**

- Universal 120-277 VAC input voltage
- Auxiliary 12V output.
- 0-10V dimming standard for a dimming range of 100% to 10%.
- THD: ≤20%
- Power Factor: ≥90%
- Operating Temperature Range: -30°C to 50°C

**Controls:**

- Optional Motion sensor
- Optional Emergency Battery

**Lifespan:**

- Estimated 100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

**Warranty:**

- 5 Year limited warranty

**Certification:**

- UL cUL wet location listed
- NEMA4X approved

**Mount:**

- Suspension and surface mount option

**IP:**

- IP65 & IK08

*NOTE- Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25°C(±5°C) specifications subject to change without notice.*







### ORDERING GUIDE

SAMPLE: BLS-VTLS-50-1-DDK-WH-M-BB-F


-  -  -  -  -  -  -  -  -

MODEL	WATTAGE	VOLTAGE	CCT	FINISH	SENSOR	EMERGENCY BATTERY	LENS	INTERNAL CODE
BLS-VTLS	50 50W 90 90W	1 120-277V	DDK Adjustable Color Temperature	WH White	M Motion Sensor  BLANK Without Motion Sensor	BB Battery Back-Up  BLANK Without Battery Backup	F Frosted	Blank Alphanumeric

## ACCESSORIES


 <p>Mounting Bracket (Default)</p>	 <p>Emergency Battery 8W 900lm 90min (Sold separately)</p>	 <p>Microwave Sensor NO.: HD027VCR Description: 12VDC input (Sold separately)</p>
 <p>Chain Description: 30cm long (Default)</p>	 <p>Hardware bag (Default)</p>	 <p>Aircraft Cable Description: 3m long (Sold separately)</p>

## DIMENSIONS



## CCT AND WATTAGE SELECTABLE

This fixture has the function of adjusting the lumens output and color temperature on-site



**WATTAGE SELECT**

LV1    LV2    LV3

Each model supports 3 positions wattage regulation: LV1, LV2, LV3

**CCT SELECT**

3500K    4000K    5000K

Offer three CCT adjustable (3500K, 4000K, 5000K).

## PERFORMANCE DATA

50W 4FT							
SETTING	SYSTEM WATTS	3500K		4000K		5000K	
		LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)
LV1	50W	6700lm	134 lm/W	7100lm	142 lm/W	6900lm	138 lm/W
LV2	35W	4780lm	137 lm/W	5100lm	146 lm/W	4900lm	140 lm/W
LV3	25W	3500lm	140 lm/W	3800lm	152 lm/W	3560lm	142 lm/W

90W 8FT							
SETTING	SYSTEM WATTS	3500K		4000K		5000K	
		LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)
LV1	90W	12200lm	136 lm/W	12800lm	142 lm/W	12500lm	139 lm/W
LV2	75W	10300lm	137 lm/W	10800lm	144 lm/W	10500lm	140 lm/W
LV3	60W	8300lm	138 lm/W	8800lm	147 lm/W	8500lm	142 lm/W